

Pneumatic Tilt Tables

Pneumatic Tilt Tables



Model Number	Tilt Capacity	Degree of Tilt	Lowered Height	Base Size W / L	Platform Size W / L	Shipping Weight
AT10 Series						
AT10 - 3648	1000 lbs	30°	7"	36" x 48"	36" x 48"	640 lbs
AT10 - 4848	1000 lbs	30°	7"	36" x 48"	48" x 48"	700 lbs
AT10 - 4856	1000 lbs	30°	7"	36" x 48"	48" x 56"	750 lbs
AT10 - 4860	1000 lbs	30°	7"	36" x 48"	48" x 60"	770 lbs
AT20 Series						
AT20 - 3648	2000 lbs	30°	7"	36" x 48"	36" x 48"	690 lbs
AT20 - 4848	2000 lbs	30°	7"	36" x 48"	48" x 48"	770 lbs
AT20 - 4856	2000 lbs	30°	7"	36" x 48"	48" x 56"	835 lbs
AT20 - 4860	2000 lbs	30°	7"	36" x 48"	48" x 60"	855 lbs
AT40 Series						
AT40 - 4848	4000 lbs	30°	7"	36" x 48"	48" x 48"	795 lbs
AT40 - 4856	4000 lbs	30°	7"	36" x 48"	48" x 56"	850 lbs
AT40 - 4860	4000 lbs	30°	7"	36" x 48"	48" x 60"	880 lbs
AT60 Series						
AT60 - 4848	6000 lbs	30°	8"	48" x 48"	48" x 48"	890 lbs
AT60 - 4856	6000 lbs	30°	8"	48" x 48"	48" x 56"	970 lbs
AT60 - 4860	6000 lbs	30°	8"	48" x 48"	48" x 60"	1040 lbs

Features

- 2000 - 6000 lb. capacity
- 30° tilt
- Air requirements 80 psi at 15 cfm
- Standard pedestal control
- Foot control available
- Optional floor stand available
- Pressure relief valve standard
- Optional fork pockets
- Lifetime warranty on actuator
- Optional motion stabilizer
- Custom designs available
- Restraining chain to guard against over tilt
- 35° & 45° tilt available, consult sales

Pneumatic Options

Mechanical Options

Description and Specification
Oversized Platform - platforms can be increased in width and length up to additional 24". Side and end load capacities are derated 2% per inch of increase and oversized models must be lagged to the floor.
Platform with Beveled Edges - welded at 30° angles, increases the standard platform by 4" on all sides.
Pit Mounted Units - for ground level applications require a Platform with Beveled Edges. Lifting Eyes required for installation.
Lifting Eyes - provided for installation and transporting of unit with a sling or lifting chain.
Portable Units - wheeled dolly handle and two 5" fixed wheels (specify side or end mounting) for moving empty lifts. Overall lowered height is not changed when unit is in an operating position. Only available on AXS, AXSR, and AXST. Oversized platform available.
Transportable Units - 6" steel casters, two fixed and two swivel, and a Presto floor lock mounted underneath base frame. Adds 9 3/4" to the lowered height. Only available on AXS, AXSR, and AXST. Oversized platform available.
V Grooved Wheels - 5" steel wheels for Transportable Units only, sold per pair.
Heavy-duty turntables available.

Description and Specification
Detent Stops - manual or spring activated stops for a Turntable, standard stops positioned at 90° increments.
Positioning Lock - Pneumatically actuated lock for turntable tops, securely locks the turntable in any position. Must be used in conjunction with a Turret bearing system.
Conveyor Top - mounted to the lift table platform, these 1.9" diameter rollers on 3" center have a 1000 lb capacity per linear foot. Adds 4" to overall height.
Optional Top Material - for special handling of loads, v tops, aluminum material, stainless steel, diamond plate, etc.
Accordion (Bellows) Skirts - designed to cover the scissor leg assembly of the lift table.
Fork Pockets - used for moving scissor lifts between work stations.
Floor Stands - designed to increase the lowered height of tilters.
Motion Stabilizer - reduces the "bounce" found in pneumatic tilt tables.